PART #NVERXV3TKUSBC

EZGO RXV ULTRA SEAL ENCLOSURE & BAG COVER INSTALLATION INSTRUCTIONS

PARTS NEEDED FOR ENCLOSURE INSTALLATION:

Track style enclosure

Driver side aluminum awning rail (1)

Passenger side aluminum awning rail (1)
Rear aluminum awning rail (1)

Taptite screws (9)

ENCLOSURE INSTALLATION:

- Remove tubes from enclosure and zip onto front canopy struts. See Picture 1.
- Place side rail so that back corner is flush with rear canopy strut pocket and front is aligned with tube. Channel should be towards outside and notch towards front.
- Mark and drill outside holes using 5/32" bit. Attach using 2 screws. Drill center hole and install screw. See Picture 2. Repeat for other side. Install rear rail by aligning ends of rail with edge of rear canopy strut pocket. Mark and drill outside holes using 5/32" bit. Attach with 2 screws. Mark and drill center hole and install screw. See Picture 3.
- Install rear and side enclosure panels by sliding them into the aluminum awning rails. See Picture 4.

Attach closeout panel to seat back using the adhesive backed hook and loop strip. See Picture 5. Install rear closeout panel by attaching to side panels with hook and loop (plastic bead should align with the bead on the side panels). Tuck bead under seat

PARTS NEEDED FOR BAG COVER INSTALLATION (IF INCLUDED):

BAG COVER INSTALLATION: Club Protector bag cover

Aluminum awning rail (1)

Taptite screws (3)

- Remove rear most nuts and bolts from bag hoop assembly. Retain hardware.
- Attach bottom bag cover bar using hardware removed in step #1. See Picture 6.
- Center the awning rail between the rear canopy struts. Use rail as a guide to mark and drill 5/32" holes. Attach rail using 3 screws. See Picture 7.

